

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

CLAIMS

Please amend the claims as follows:

1. (Presently amended) A method ~~(200)~~ for automatically establishing an isochronous signal for transmission to a signal receiving device, the method comprising:

using a serial bus ~~(80)~~ responsive to a set-top device ~~(10)~~ and a first signal receiving device ~~(12)~~, ~~the serial bus (80) having an architecture defined by an Institute of Electrical and Electronics Engineers ("IEEE") 1394 specification;~~

discovering ~~(202)~~ a signal receiving capability of the first signal receiving device ~~(12)~~, wherein the discovering occurs by having the first signal receiving device broadcasting self-ID packets over the serial bus and the set-top device establishing an asynchronous transaction with the first signal receiving device so as to receive configuration data from the first signal receiving device; and

without user intervention, based on the discovered signal receiving capability, producing ~~(204)~~ an isochronous signal ~~(14)~~ for transmission to the first signal receiving device ~~(12)~~ over the serial bus ~~(80)~~.

2. (Presently amended) The method according to claim 1, further comprising:

transmitting the produced isochronous signal ~~(14)~~ to the first signal receiving device ~~(12)~~ over the serial bus ~~(80)~~.

3. (Presently amended) The method according to claim 1, further comprising:

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

providing the serial bus (80) between the first signal receiving device (12) and a second signal receiving device (302/304); and

discovering a signal receiving capability of the second signal receiving device (302/304).

4. (Presently amended) The method according to claim 3, wherein the step of producing the isochronous signal (14) for transmission comprises producing the isochronous signal (14) for transmission to one of the first (12) and second (302/304) signal receiving devices.

5. (Presently amended) The method according to claim 4, wherein the set-top device (10) supports a single isochronous point-to-point connection on the serial bus (80).

6. (Presently amended) The method according to claim 4, further comprising:

determining which one of the first signal receiving device (12) and the second signal receiving device (302/304) is closest to the set-top device (10), by causing a ping packet to be sent to the first signal receiving device (12) and the second signal receiving device (302/304), and measuring an amount of time it takes for each of the first and second signal receiving devices to return data based on the ping packet; and

based on the measured amount of time, producing the isochronous signal (14) for transmission to the signal receiving device closest to the set-top device.

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

7. (Presently amended) The method according to claim 1, wherein digital content is transmittable from the set-top device (10) to the first signal receiving device (12) via the serial bus (80), and wherein analog content is transmittable from the set-top device (10) to the first signal receiving device (12) via an analog interface (82).

8. (Presently amended) The method according to claim 7, further comprising:

determining if the first signal receiving device (12) is responsive to the analog interface (82).

9. (Presently amended) The method according to claim 8, wherein the ~~step of~~ determining comprises measuring a resistance associated with the analog interface (82).

10. (Presently amended) The method according to claim 8, wherein the ~~step of~~ determining comprises assuming the first signal receiving device (12) is not responsive to the analog interface (82).

11. (Presently amended) The method according to claim 8, further comprising:

when the first signal receiving device (12) is not responsive to the analog interface (82), producing a message for transmission to the first signal receiving device over the serial bus.

12. (Presently amended) The method according to claim 11, wherein the message comprises an on-screen display of a digital television signal, informing a user that an

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

analog connection between the set-top device (40) and the first signal receiving device (42) is desirable.

13. (Presently amended) A computer-readable storage medium (64) encoded with a computer program (22) which, when loaded into a processor (39), implements the method of claim 1.

14. (Presently amended) An apparatus for automatically establishing an isochronous signal (14) for transmission to a signal receiving device (12), the apparatus comprising:

a computer-readable storage medium (64); and

a processor (39) responsive to the computer-readable storage medium (64) and to a computer program (22), the computer program (22), when loaded into the processor (39), operative to perform a method (200) comprising:

using a serial bus responsive to a set-top device and the signal receiving device; ~~the serial bus having an architecture defined by an IEEE 1394 specification;~~

discovering (202) a signal receiving capability of the first signal receiving device wherein the discovering occurs by having the first signal receiving device broadcasting self-ID packets over the serial bus and the set-top device establishing an asynchronous transaction with the first signal receiving device so as to receive configuration data from the first signal receiving device; and

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

without user intervention, based on the discovered signal receiving capability, producing (204) an isochronous signal for transmission to the signal receiving device over the serial bus.

15. (Presently amended) A set-top device (10) for use within a broadband communications system, comprising:

an interface (61) to a serial bus (80), the serial bus (80) responsive to a signal receiving device (12) ~~and having an architecture defined by IEEE 1394 specification:~~

a processor (39);

a computer readable storage medium (64) encoded with a computer program (22) which, when loaded into the processor (39), is operative to perform a method (200) comprising:

discovering (202) a signal receiving capability of the signal receiving device wherein the discovering occurs by having the first signal receiving device broadcasting self-ID packets over the serial bus and the set-top device establishing an asynchronous transaction with the first signal receiving device so as to receive configuration data from the first signal receiving device; and

without user intervention, based on the discovered signal receiving capability, producing (204) an isochronous signal for transmission to the signal receiving device via the interface to the serial bus.

16. (Presently amended) The set-top device (10) according to claim 15, wherein the set-top device (10) comprises one of a cable set-top device and a terrestrial set-top device.

App. Ser. No.: 10/825,644

Atty. Doc. No.: D03125

17. (Presently amended) The set-top device ~~(10)~~ according to claim 16, wherein the isochronous signal ~~(14)~~ comprises a displayable digital television signal.
18. (Original) The method according to claim 17, wherein the displayable digital television signal comprises one of an on-screen display and a signal for recording by a recording device.
19. (Presently amended) The set-top device ~~(10)~~ according to claim 16, wherein the signal receiving device ~~(12)~~ comprises one of a display device, a digital video cassette recorder, a hard disk drive; a digital video camera recorder; and a digital video disk recorder.
20. (Original) The set-top device according to claim 19, wherein the broadband communications system comprises a cable television system.